PS303H DC Power Supply



Features

- 0~30V 0~3A regulable
- · 4 digit LED display
- High as 80% power efficiency
- Full protection such as current-limit, short-circuit, over-heat, over-voltage.
- · A secondary MOS linear circuit (with patent) ensuring a super voltage stability
- Small size as 3U high appropriately fit for work station or test equipment rack

Occasions and Applications

- Provide power source for factory maintenance, calibration positions
- Built in test equipment rack cabinet and supply power
- Power the DIY kits and circuits in our work bench
- A neccesary tool for educational institute particularly for those involve electronics and tele-communication majorities.







PS303H DC Power Supply

Technical Specifications

Input	110V/220V AC switchable
Output:	0~30V, 0~3A regulated
LED display	4 digit LED ±0.5%±1
Dimension:	226*82*138mm
Net Weight:	1.8kg
Working temperature:	0 ~ 40°C
Relative humidity:	≤ 80%
VOLTAGE REGULAT	ON
Regulation rate:	≤ 0.05% + 3mV
Load regulation rate:	≤ 0.1% + 3mV (Rated Current ≤ 3A)
	≤ 0.1% + 5mV (Rated Current> 3A)
Riple and noice:	≤5mVrms (5Hz ~ 1MHz)
CURRENT REGULAT	ION
Regulation rate:	≤ 0.2% + 3mA
load regulation rate:	≤ 0.2% +6mA
Riple and noice:	≤ 10mArms
Restore:	≤ 300µs (with load of 50% regulation rate, 0.5A.)
HIGH VOLTAGE	
Leak current	≤1mA (with input 1500VAC/1s to ground)
Insulant resistance:	≥5MΩ (with input 500VDC/Ss to ground)
RESTORE CONDITIO	NS
Temperature:	-10 ~ 70°C
Relative humidity:	≤ 70%

Product Lineum

Regulated DC Power Supply, Power Module, GSM Alarm System, PIR motion senor, Door Sensor





