# PS305H DC Power Supply



#### Features

- 0~30V 0~5A regulable
- 4 digit high precision display
- High as 80% power efficiency
- Full protection such as current-limit, short-circuit, over-heat, over-voltage.
- A secondary MOS linear circuit (with patent) ensuring a super voltage stability
- . Small size as 3U high appropriately fit for work station or test equipment rack

### **Occasions and Applications**

- Provide power source for factory maintenance, calibration positions
- Built in test equipment rack cabinet and supply power
- Power the DIY kits and circuits in our work bench
- A neccesary tool for educational institute particularly for those involve electronics and tele-communication majorities.







## PS305H DC Power Supply

# **Technical Specifications**

| GENERAL INFORMATION   |   |
|-----------------------|---|
| Input:                | 110V/220V AC switchable                           |
| Output:               | 0~30V, 0~5A regulated                             |
| LED display           | 4 digit LED ±0.5%±1                               |
| Dimension:            | 226*82*138mm                                      |
| Net Weight:           | 1.8kg   |
| Working temperature:  | 0 ~ 40°C  |
| Relative humidity:    | ≤ 80%   |
| VOLTAGE REGULAT       | ION   |
| Regulation rate:      | ≤ 0.05% + 3mV                                     |
| Load regulation rate: | ≤ 0.1% + 3mV (Rated Current ≤ 3A)                 |
|                       | ≤ 0.1% + 5mV (Rated Current> 3A)                  |
| Riple and noice:      | ≤5mVrms (5Hz ~ 1MHz)                              |
| CURRENT REGULAT       | ION   |
| Regulation rate:      | ≤ 0.2% + 3mA                                      |
| load regulation rate: | ≤ 0.2% +6mA                                       |
| Riple and noice:      | ≤ 10mArms   |
| Restore:              | ≤ 300µs (with load of 50% regulation rate, 0.5A.) |
| HIGH VOLTAGE          |   |
| Leak current:         | ≤1mA (with input 1500VAC/1s to ground)            |
| Insulant resistance:  | ≥5MΩ (with input 500VDC/5s to ground)             |
| RESTORE CONDITIO      | NS  |
| Temperature:          | -10 ~ 70°C  |
| Relative humidity:    | ≤ 70%   |
|                       |   |

Product Lineum

Regulated DC Power Supply, Power Module, GSM Alarm System, PIR motion senor, Door Sensor





